

Theory of Network Communication

Fall 2004

Assignment 4

Problem 9 (4 points):

Our goal in this problem will be to show that NTO is universally stable. We prove this by induction. Consider any (w, λ) -bounded adversary with $\lambda = 1 - \epsilon$ where $\epsilon > 0$.

- (a) Show, as the induction basis, that at any time, the maximum number of times a packet is delayed at its first edge is at most w/ϵ . Suppose otherwise, i.e. some packet experiences a delay of more than w/ϵ , and let e be any edge at which this happens. Let t denote the corresponding time step, and let us follow e backwards in time till we reach the first time point t' at which no packet is waiting at e that has not traversed any edge so far. Consider the sequence of time steps $I = \{t' + 1, t' + 2, \dots, t\}$, i.e. $|I| = t - t'$. Argue that all packets that were moved along e during I must have been generated during I . Use this to show that this means that $\lambda(|I| + w) \geq |I|$, which leads to a contradiction when using our assumption above. Thus, any packet needs at most $(w + 1)/\epsilon$ steps to traverse its first edge. (2 points)

- (b) Suppose that it has already been shown that every packet traveling along a path of length at most d needs at most

$$\sum_{i=1}^d \frac{w+1}{\epsilon^i}$$

time steps for this. But suppose that it is possible for a packet to be delayed at least $(w + 1)/\epsilon^{d+1}$ times while waiting to cross its $(d + 1)$ st edge. Show in a similar argument as in (a) that in this case, for the sequence of time steps I ,

$$\lambda \left(\sum_{i=1}^d \frac{w+1}{\epsilon^i} + |I| + w \right) \geq |I|$$

Use this to prove a contradiction. (2 points)

Thus, the same worst-case time bound can be shown for NTO as for SIS.

Problem 10 (3 points):

Show that for $\lambda \geq 0.76$ there is a network and an adversary that causes NTG to be unstable. (Hint: use the same strategy as for FIFO.)

Problem 11 (3 points):

Use the techniques in the E-program “xy-mesh-router.e”, which is available on the course web page, to write an E-program that implements a routing service for the bit adjustment strategy in a hypercube.