

Lecture 24

Note Title

Swendsen-Wang.

Ising $X_i \in \{-1, 1\}$
Edges E .

5/21/2006

Standard Metropolis is slow to converge when sampling from the Ising Model.

$$P(\underline{x}) = \frac{1}{Z} e^{\sum_{i,j \in E} X_i X_j / T}$$

particularly slow at low temperature.

Swendsen-Wang (SW) is a way to speed up the sampling by "dynamically grouping" sites into clusters.

Then the state of the entire cluster can be switched.

SW is also an example of Data Augmentation:

page 2.

Swendsen-Wang

(*) Each subset V_i is connected.

First, Swendsen-Wang for the Potts model.

Each node s , can take colors $c_s \in \{1, 2, \dots, Q\}$

$$P(c) = \frac{1}{Z} e^{\beta \sum_{s,t \in E} I(c_s = c_t)}$$

$$\left\{ \begin{array}{l} I(c_s = c_t) = 1, \text{ if } c_s = c_t \\ = 0, \text{ otherwise} \end{array} \right\}$$


Ising model is a special case of Potts with $Q = 2$.

Notation: set of nodes V , partition into subsets $\{V_i; i=1 \dots n\}$

such that $\bigcup_{i=1}^n V_i = V$, $V_i \cap V_j = \emptyset$, $\forall i \neq j$.


All nodes in each subset have the same color.

state A



$$\Pi_A = (V_0 \cup V_1, V_2)$$

state B



$$\Pi_B = (V_0, V_1 \cup V_2)$$

Partitions differ only by the state of the regions.

SW Algorithm.

1. Define a new variable $V_{s,t}$ (binary-valued).
 Set. $V_{s,t} = 0$ if $c_s \neq c_t$.
 If $c_s = c_t$, set $V_{s,t} = 1$ with prob
 $q_0 = 1 - e^{-\beta}$, (otherwise $V_{s,t} = 0$).

This yields a number of connected components (each is a subset of vertices of the same colour).

2. Randomly select a connected component (e.g. the \vdots region on previous page).
3. Randomly select a color for this connected component (uniform prob).

Claim: this algorithm is a Markov Chain Monte Carlo. - satisfies detailed balance.

It encodes large groups at small temperature (large β)

Page 4

Detailed Balance of SW.

Define: $C_A = C(V_0, V_1) = \{ (s, t) : s \in V_0, t \in V_1 \}$
 $C_B = C(V_0, V_2) = \{ (s, t) : s \in V_0, t \in V_2 \}$

These are the Swendsen-Wang cuts at π_A, π_B

Then, it follows that:

$$\frac{q(\pi_A \rightarrow \pi_B)}{q(\pi_B \rightarrow \pi_A)} = \frac{(1-q_0)^{|C_A|}}{(1-q_0)^{|C_B|}}$$

where $|C_A|, |C_B|$ are the sizes of C_A & C_B .

For the Potts model.

$$\frac{p(\pi_A)}{p(\pi_B)} = \frac{e^{-\beta|C_B|}}{e^{-\beta|C_A|}}$$

Hence: if we set $q_0 = 1 - e^{-\beta}$,

then

$$\frac{q(\pi_B \rightarrow \pi_A)}{q(\pi_A \rightarrow \pi_B)} \frac{p(\pi_B)}{p(\pi_A)} = 1$$

which is detailed balance.

Alternative View of Swendsen-Wang.
on Potts model.

$$\pi(\underline{c}) \quad \pi(\underline{v} | \underline{c}) = \prod_{s,t \in E} \pi(v_{s,t} | c_s, c_t)$$

with $\pi(v_{s,t}=1 | c_s, c_t) = 0$, if $c_s \neq c_t$
 $\pi(v_{s,t}=1 | c_s, c_t) = 1 - e^{-\beta}$, if $c_s = c_t$

Then do Data Augmentation:

Fix \underline{c} ,
 sample from $\pi(\underline{v} | \underline{c})$ to get
 connected components.

Then sample from $\pi(\underline{c} | \underline{v})$ to get the
 colour of the connected components.

It can be shown that $\pi(\underline{c} | \underline{v})$ is
 a uniform distribution on each colour for
 each connected component.

(By definition, each connected component
 must have the same colour).

Page 6.

Extending Swendsen-Wang (Barbu & Zhu)

Standard SW is restricted to a few special distributions — e.g. Ising model & Potts model.

The problem is that detailed balance only occurs for these models.

But, we can extend Swendsen-Wang by Metropolis-Hastings.

Use SW to make proposals

$q(\pi_A \rightarrow \pi_B)$, then accept proposals with probability

$$\alpha(\pi_A \rightarrow \pi_B) = \min \left(1, \frac{q(\pi_B \rightarrow \pi_A) p(\pi_B)}{q(\pi_A \rightarrow \pi_B) p(\pi_A)} \right)$$

(Note: original SW is a special case where $\alpha(\pi_A \rightarrow \pi_B) = 1$, the proposal is automatically accepted because of detailed balance.)