

# Zero-Knowledge Proofs - II

CS 601.642/442 Modern Cryptography

Fall 2019

# Zero-Knowledge Proofs for **NP**

## Theorem

*If one-way permutations exist, then every language in **NP** has a zero-knowledge interactive proof.*

- The assumption can in fact be relaxed to just one-way functions
- Think: How to prove the theorem?
- Construct ZK proof for every **NP** language?
- Not efficient!

# Zero-Knowledge Proofs for **NP** (contd.)

## Proof Strategy:

**Step 1:** Construct a ZK proof for an **NP**-complete language. We will consider *Graph 3-Coloring*: language of all graphs whose vertices can be colored using only three colors s.t. no two connected vertices have the same color

**Step 2:** To construct ZK proof for any **NP** language  $L$ , do the following:

- Given instance  $x$  and witness  $w$ ,  $P$  and  $V$  reduce  $x$  into an instance  $x'$  of Graph 3-coloring using Cook's (deterministic) reduction
- $P$  also applies the reduction to witness  $w$  to obtain witness  $w'$  for  $x'$
- Now,  $P$  and  $V$  can run the ZK proof from Step 1 on common input  $x'$

# Physical ZK Proof for Graph 3-Coloring

- Consider graph  $G = (V, E)$ . Let  $C$  be a 3-coloring of  $V$  given to  $P$
- $P$  picks a random permutation  $\pi$  over colors  $\{1, 2, 3\}$  and colors  $G$  according to  $\pi(C)$ . It hides each vertex in  $V$  inside a locked box
- $V$  picks a random edge  $(u, v)$  in  $E$
- $P$  opens the boxes corresponding to  $u, v$ .  $V$  accepts if  $u$  and  $v$  have different colors, and rejects otherwise
- The above process is repeated  $n|E|$  times
- **Intuition for Soundness:** In each iteration, cheating prover is caught with probability  $\frac{1}{|E|}$
- **Intuition for ZK:** In each iteration,  $V$  only sees something it knew before – two random (but different) colors

# Towards ZK Proof for Graph 3-Coloring

- To “digitize” the above proof, we need to implement locked boxes
- Need two properties from digital locked boxes:
  - **Hiding:**  $V$  should not be able to see the content inside a locked box
  - **Binding:**  $P$  should not be able to modify the content inside a box once its locked

# Commitment Schemes

- Digital analogue of locked boxes
- Two phases:
  - Commit phase: Sender locks a value  $v$  inside a box
  - Open phase: Sender unlocks the box and reveals  $v$
- Can be implemented using interactive protocols, but we will consider non-interactive case. Both commit and reveal phases will consist of single messages

# Commitment Schemes: Definition

## Definition (Commitment)

A randomized polynomial-time algorithm  $\text{Com}$  is called a *commitment scheme* for  $n$ -bit strings if it satisfies the following properties:

- **Binding:** For all  $v_0, v_1 \in \{0, 1\}^n$  and  $r_0, r_1 \in \{0, 1\}^n$ , it holds that  $\text{Com}(v_0; r_0) \neq \text{Com}(v_1; r_1)$
- **Hiding:** For every non-uniform PPT distinguisher  $D$ , there exists a negligible function  $\nu(\cdot)$  s.t. for every  $v_0, v_1 \in \{0, 1\}^n$ ,  $D$  distinguishes between the following distributions with probability at most  $\nu(n)$ 
  - $\{r \xleftarrow{\$} \{0, 1\}^n : \text{Com}(v_0; r)\}$
  - $\{r \xleftarrow{\$} \{0, 1\}^n : \text{Com}(v_1; r)\}$

## Commitment Schemes: Remarks

- The previous definition only guarantees hiding for one commitment
- **Multi-value Hiding:** Just like encryption, we can define multi-value hiding property for commitment schemes
- Using hybrid argument (as for public-key encryption), we can prove that any commitment scheme satisfies multi-value hiding
- **Corollary:** One-bit commitment implies string commitment



# Construction of Bit Commitments

**Construction:** Let  $f$  be a OWP,  $h$  be the hard core predicate for  $f$

**Commit phase:** Sender computes  $\text{Com}(b; r) = f(r), b \oplus h(r)$ . Let  $C$  denote the commitment.

**Open phase:** Sender reveals  $(b, r)$ . Receiver accepts if  $C = (f(r), b \oplus h(r))$ , and rejects otherwise

**Security:**

- Binding follows from construction since  $f$  is a permutation
- Hiding follows in the same manner as IND-CPA security of public-key encryption scheme constructed from trapdoor permutations

# ZK Proof for Graph 3-Coloring

**Common Input:**  $G = (V, E)$ , where  $|V| = n$

**$P$ 's witness:** Colors  $\text{color}_1, \dots, \text{color}_n \in \{1, 2, 3\}$

**Protocol  $(P, V)$ :** Repeat the following procedure  $n|E|$  times *using fresh randomness*

$P \rightarrow V$ :  $P$  chooses a random permutation  $\pi$  over  $\{1, 2, 3\}$ . For every  $i \in [n]$ , it computes  $C_i = \text{Com}(\widetilde{\text{color}}_i)$  where  $\widetilde{\text{color}}_i = \pi(\text{color}_i)$ . It sends  $(C_1, \dots, C_n)$  to  $V$

$V \rightarrow P$ :  $V$  chooses a random edge  $(i, j) \in E$  and sends it to  $P$

$P \rightarrow V$ : Prover opens  $C_i$  and  $C_j$  to reveal  $(\widetilde{\text{color}}_i, \widetilde{\text{color}}_j)$

$V$ : If the openings of  $C_i, C_j$  are valid and  $\widetilde{\text{color}}_i \neq \widetilde{\text{color}}_j$ , then  $V$  accepts the proof. Otherwise, it rejects.

# Proof of Soundness

- If  $G$  is not 3-colorable, then for any coloring  $\text{color}_1, \dots, \text{color}_n$ , there exists at least one edge which has the same colors on both endpoints
- From the binding property of  $\text{Com}$ , it follows that  $C_1, \dots, C_n$  have unique openings  $\widetilde{\text{color}}_1, \dots, \widetilde{\text{color}}_n$
- Combining the above, let  $(i^*, j^*) \in E$  be s.t.  $\widetilde{\text{color}}_{i^*} = \widetilde{\text{color}}_{j^*}$
- Then, with probability  $\frac{1}{|E|}$ ,  $V$  chooses  $i = i^*, j = j^*$  and catches  $P$
- In  $n|E|$  independent repetitions,  $P$  successfully cheats in all repetitions with probability at most

$$\left(1 - \frac{1}{|E|}\right)^{n|E|} \approx e^{-n}$$

# Proving Zero Knowledge: Strategy

- Will prove that a single iteration of  $(P, V)$  is zero knowledge
- For the full protocol, use the following (read proof online):

## Theorem

*Sequential repetition of any ZK protocol is also ZK*

- To prove that a single iteration of  $(P, V)$  is ZK, we need to do the following:
  - Construct a Simulator  $S$  for every PPT  $V^*$
  - Prove that expected runtime of  $S$  is polynomial
  - Prove that the output distribution of  $S$  is correct (i.e., indistinguishable from real execution)
- Intuition for proving ZK for a single iteration:  $V$  only sees two random colors. Hiding property of Com guarantees that everything else remains hidden from  $V$ .

# Proving Zero Knowledge: Simulator

**Simulator**  $S(x = G, z)$ :

- Choose a random edge  $(i', j') \xleftarrow{\$} E$  and pick random colors  $\text{color}'_{i'}, \text{color}'_{j'} \xleftarrow{\$} \{1, 2, 3\}$  s.t.  $\text{color}'_{i'} \neq \text{color}'_{j'}$ . For every other  $k \in [n] \setminus \{i', j'\}$ , set  $\text{color}'_k = 1$
- For every  $\ell \in [n]$ , compute  $C_\ell = \text{Com}(\text{color}'_\ell)$
- Emulate execution of  $V^*(x, z)$  by feeding it  $(C_1, \dots, C_n)$ . Let  $(i, j)$  denote its response
- If  $(i, j) = (i', j')$ , then feed the openings of  $C_i, C_j$  to  $V^*$  and output its view. Otherwise, restart the above procedure, at most  $n|E|$  times
- If simulation has not succeeded after  $n|E|$  attempts, then output **fail**

## Hybrid Experiments:

- $H_0$ : Real execution
- $H_1$ : Hybrid simulator  $S'$  that acts like the real prover (using witness  $\text{color}_1, \dots, \text{color}_n$ ), except that it also chooses  $(i', j') \xleftarrow{\$} E$  at random and if  $(i', j') \neq (i, j)$ , then it outputs **fail**
- $H_2$ : Simulator  $S$

## Correctness of Simulation (contd.)

- $H_0 \approx H_1$ : If  $S'$  does not output **fail**, then  $H_0$  and  $H_1$  are identical. Since  $(i, j)$  and  $(i', j')$  are independently chosen,  $S'$  fails with probability at most:

$$\left(1 - \frac{1}{|E|}\right)^{n|E|} \approx e^{-n}$$

Therefore,  $H_0$  and  $H_1$  are statistically indistinguishable

- $H_1 \approx H_2$ : The only difference between  $H_1$  and  $H_2$  is that for all  $k \in [n] \setminus \{i', j'\}$ ,  $C_k$  is a commitment to  $\pi(\text{color}_k)$  in  $H_1$  and a commitment to 1 in  $H_2$ . Then, from the multi-value hiding property of  $\text{Com}$ , it follows that  $H_1 \approx H_2$

## Additional Reading

- Zero-knowledge Proofs for Nuclear Disarmament [Glaser-Barak-Goldston'14]
- Non-black-box Simulation [Barak'01]
- Concurrent Composition of Zero-Knowledge Proofs [Dwork-Naor-Sahai'98, Richardson-Kilian'99, Kilian-Petrank'01, Prabhakaran-Rosen-Sahai'02]
- Non-malleable Commitments and ZK Proofs [Dolev-Dwork-Naor'91]