



Image Texture Fundamentals

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



Texturing

Allows higher-frequency color variation

- Not just interpolated from vertex colors

May be 2D (surface-based) or 3D (volume-based)

- (or even 4D for light fields -- that's a different lecture)

May be strictly image-based or procedural

- Today we'll talk about simple image-based

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



2D Texture Mapping

Requires surface parameterization

- Mapping from 3D surface to 2D parametric domain


Colors defined in 2D parameter space

Parameterization (texture coordinates) used to determine material color at point on surface

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



2D Texture Diagram



Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



2D Texture Applications


Most useful for colors that are sitting on the surface, rather than running through the material

- Pictures on the wall
- Printed/painted logos, text, etc.
- Fake wood grain

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



2D Texture Example



Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



Other Types of 2D Maps

Bump/normal maps

- Modify or define surface normals

Displacement maps

- Modify surface itself

Environment/reflection maps

- Define environment seen in specular reflections

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



3D Texture Maps

Colors defined in 3D space


3D coordinates of surface used for mapping

Usually convenient to define 3D texture in object space

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



Bump (normal) Map Example



Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



3D Texture Applications

More like carving object out of material than pasting a picture on the surface

- wood, marble, etc.
- clouds, fog, fire (hypertextures, using additional density information)

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



Image-based Texture Mapping (2D)

2D texel array (image) determines colors in texture domain

Given texture coordinates on surface, look up color in image

Lookup may return nearest texel (*point sampled*) or bilinear interpolation of 4 surrounding texels

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



Acquiring Texture Images

Photograph


- flat surface
- even lighting (no specularity)


3D Rendering

Procedural synthesis

- Sample a procedural texture


Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen

 **Texture Sampling**



from Heckbert, Paul. *Fundamentals of Texture Mapping and Image Warping*. Masters Thesis. UC Berkeley. 1989. page 7.

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen

 **Sampling Approaches**

Point Sampling

- Pick closest texel
- (Replication/pixel zoom for upsampling)


Interpolation


- Blend closest texels

Area Sampling

- Blend all covered texels

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen

 **Bilinear Interpolation**




$p = (p_s, p_t)$

$p' = ((p_s - a_s) / (b_s - a_s), (p_t - a_t) / (c_t - a_t))$

$p_{color} = \text{lerp}(\text{lerp}(a_{color}, b_{color}, p_s'), \text{lerp}(c_{color}, d_{color}, p_t'), p_t')$

$\text{lerp}(k_1, k_2, t) = (1-t)*k_1 + t*k_2$

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen

 **Texture Area Sampling**


If frequency of texture content is higher than sampling rate, may want better filtering

Pixel-sized area on surface covers some area in texture domain

- Curvilinear quadrilateral or ellipse

Perform weighted average of texels covered by pixel-sized piece of surface

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen

 **Mip-mapped Texture Filtering**


Multim im parvo (many things in a small place)


Pre-compute *image pyramid* to filter texture to various resolutions

Look up colors from the appropriate level(s) of the image pyramid

Approximation to accurate area sampling


Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen


 **Image Pyramid**




parent color = average(4 children colors)

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen

 **Mip-map Organization**



Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen


 **Mip-map Filtering Methods**

Compute d , the parameter along level space

Sample texture

- Option 1: Point sample nearest level
- Option 2: Point sample each adjacent level, then linearly interpolate between them
- Option 3: Choose nearest level, then bilinearly interpolate within that level
- Option 4: Trilinearly interpolate between the 8 samples of two adjacent mip-map levels (2 bilinear interps + 1 linear)

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen

 **Computing d**

Somewhat tricky, because a circular footprint on the screen is elliptical in the texture domain


Typically either over-filter or under-filter

One possible formulation:

$$d = \max \left(\sqrt{(du/dx)^2 + (dv/dx)^2}, \sqrt{(du/dy)^2 + (dv/dy)^2} \right)$$

(i.e. use the larger of the ellipse dimensions)


Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen

 **Limitations of Mip-Mapping**


Assumes circular footprint of pixel in texture domain

- produces only *isotropic* filtering
- will either over-filter or under-filter in some regions (blurry or jaggy)

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen

 **Efficient Anisotropic Filtering**

Use multiple mip-map lookups to produce a non-symmetric filter



Video example: Feline





Figure 19: Trilinear paints blurry text. Figure 21: "High-efficiency" Simple Feline paints smooth text.

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen

 **3D Image-based Texture Mapping**

Store data in a 3D image (voxel grid)

Point sample using nearest voxel

Linearly interpolate using 8 nearest voxels

Pre-filtering possible using 3D analog to mip-mapping

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



Acquiring 3D images

Slice and photograph real materials

- e.g. - The Visible Human

Measure density volume using CT scan or MRI, then map densities to colors

Sample a procedurally-generated volume

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



Canonical Parameterizations

Three common primitives:

- Plane
- Cylinder
- Sphere

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



Plane Parameterization

Suppose we have a plane with origin O and non-collinear axes, i and j

- $(x,y,z) = (O_x + s i_x + t j_x, O_y + s i_y + t j_y, O_z + s i_z + t j_z)$
- $(u,v) = (s,t)$

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



Cylinder Parameterization

Suppose we have a circular cylinder of height h about z -axis (with base at $z=0$)

- $(x,y,z) = (r \cos \theta, r \sin \theta, z)$
- $(u,v) = (\theta/2\pi, z/h)$

Or we can choose to cover only a portion of the cylinder:

- $(u,v) = (a(\theta - \theta_0)/2\pi, b(z - z_0)/h)$

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



Sphere Parameterization

We can similarly parameterize the sphere:

- $(x,y,z) = (r \cos \theta \sin \phi, r \sin \theta \sin \phi, r \cos \phi)$
- $(u,v) = (\theta/2\pi, \phi/\pi)$

Note: parameterization degenerate at poles

- “you can’t comb the hair on a sphere”

Cover portion of sphere with texture:

- $(u,v) = (a(\theta - \theta_0)/2\pi, b(\phi - \phi_0)/\pi)$

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



Two-stage Mapping

1. Map texture onto canonical primitive (the intermediate surface)


2. Map intermediate surface to arbitrary object

- Position objects with respect to each other
- Project along normal direction (of either one)

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



Two-stage Example



Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



Atlas Approaches

Break complex surface into patches

Parameterize / texture each patch


- Parameterizations optimized to minimize distortions

Atlas describes mapping between texture domains and surface domain

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



Atlas Example



from Pederson, "Decorating Implicit Surfaces", *Proceedings of SIGGRAPH 95*.

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen



Other Texturing Options

Application Modes: relationship between texture colors and surface colors

- Decal - texture color replaces surface color
- Blend - colors are combined (e.g. multiplied)

Wrap modes: what to do with parameters outside of [0,1]

- Clamp
- Repeat

Johns Hopkins Department of Computer Science
Course 600.456: Rendering Techniques, Professor: Jonathan Cohen