

# **Painterly Rendering**

Johns Hopkins Department of Computer Science



# **Types of Computer Painting**

### Physical simulation

- User applies strokes
- Computer simulates media (e.g. watercolor on paper)

### **Automatic painting**

- User provides input image or 3D model and painting parameters
- Computer generates all strokes


Johns Hopkins Department of Computer Science



## **Two Painterly Rendering Systems**

- "Painterly Rendering for Animation"
  - Meier, SIGGRAPH 96
- "Painterly Rendering with Curved Brush Strokes of Multiple Sizes"
  - Hertzmann, SIGGRAPH 98

Johns Hopkins Department of Computer Science Course 600.456: Rendering Techniques, Professor: Jonathan Cohe





## **Basic Approach**

### Algorithm

- Surface particles placed in world space
- Reference images rendered
- Each particle becomes a screen-space stroke

#### **Features**

- Greater temporal coherence than purely screen-space approaches
- More natural style than purely geometry (texture-mapped) approaches

Johns Hopkins Department of Computer Science urse 600.456: Rendering Techniques, Professor: Jonathan Cohen



### **Particle Generation**

Compute area of surface primitives

Randomly place particles on primitives

• number proportional to area

Johns Hopkins Department of Computer Science



# **Reference Images**

### Used to determine stroke attributes

- color
- orientation
- size
- · many others possible

### Rendered with programmable shaders

Johns Hopkins Department of Computer Science



# **Stroke Rendering**

# Particle transformed to screen-space Stroke parameters from reference images

· perturbed according to user-specified variation

# Brush image rendered according to stroke parameters

- · oblong brush shapes work best
- grayscale brushes typically sufficient
  - —color brush textures may be used to modify particle colors

Johns Hopkins Department of Computer Science



# **Example - Haystacks**



Haystacks without random parameter perturbation



Similar view with random parameter perturbation

from Meier, "Painterly Rendering for Animation, *Proceedings of SIGGRAPH 96*, pages 481 and 478.

Johns Hopkins Department of Computer Science Course 600.456: Rendering Techniques, Professor: Jonathan Cohe




## **Example - fruit**









"Painterly
Rendering for
Animation,
Proceedings of
SIGGRAPH 96,

from Meier,

I hue variation were used to create marker-style strokes in the lower left image. The brush used to create the lower rigl que black that helps to create a woodcut print style.

Johns Hopkins Department of Computer Science ourse 600.456; Rendering Techniques, Professor; Jonathan Cohen



# **Layered Approach**

Similar objects rendered together

Dissimilar objects often rendered as separate layers and composited later

• Large strokes intrude less onto nearby objects

Johns Hopkins Department of Computer Science



## Video (or .mov movie files)

Meier, "Painterly Rendering for Animation", Proceedings of SIGGRAPH 96.

> Johns Hopkins Department of Computer Science Course 600.456; Rendering Techniques, Professor; Jonathan Coher



## Hertzmann's Approach

Apply to color images with no 3D model information

Allow longer, curved brush strokes

· makes different styles possible

Multiple rendering passes

- · larger strokes first
- · add detail with smaller strokes

Johns Hopkins Department of Computer Science



## **Stroke Description**

Constant color per stroke

**B-spline path** 

Constant radius circle (or other shape) swept along path

Applied in layers, with opacity control

Johns Hopkins Department of Computer Science



## **Building Up Layers**

Start with large strokes

Each pass reduces stroke size

New strokes placed according to error metric of current painting

Johns Hopkins Department of Computer Science Course 600.456: Rendering Techniques, Professor: Jonathan Co



### Painting a Layer

Select stroke size for layer

Blur input image

Start strokes within uniform grid cells

Start each stroke at point of maximum error within grid cell

Walk perpendicular to image gradient to place control points

Render strokes in random order as circles along cubic B-spline path

Johns Hopkins Department of Computer Science se 600.456: Rendering Techniques, Professor: Jonathan Coher



### **Style Parameters**

Approximation threshold

Brush sizes

**Curvature filter** 

**Blur Factor** 

Min/Max stroke lengths

**Opacity** 

Grid size

Color jitter

Johns Hopkins Department of Computer Science Jourse 600.456: Rendering Techniques, Professor: Jonathan Coher



## **Example Styles**

"Impressionist"

"Expressionist"

• long strokes, color value jitter


"Colorist Wash"


• transparency, RGB color jitter

"Pointillist"

densely placed circles, random hue and saturation

Johns Hopkins Department of Computer Science ourse 600.456; Rendering Techniques, Professor; Jonathan Cohen







# Video

Hertzmann, "Painterly Rendering with Curved Brush Strokes of Multiple Sizes", Proceedings of SIGGRAPH 98.

> Johns Hopkins Department of Computer Science Course 600.456: Rendering Techniques, Professor: Jonathan Col